

# **IRCUWU 2020**



INTERNATIONAL RESEARCH

# **CONFERENCE**

*"Sustainable Business Transition through Information & Knowledge Dissemination"*

# **2020**

**29 -30, July**

**Uva Wellassa University of Sri Lanka**

## **Dependence of performance of $\text{Sb}_2\text{S}_3$ thin film solar cell on blocking $\text{TiO}_2$ layer**

**M.A. Farhana and J. Bandara\***

*National Institute of Fundamental Studies, Hantana Road, Kandy, Sri Lanka*

The demand for low cost, high efficiency solar cells is the power of thin film solar cells. In recent years, antimony sulfide ( $\text{Sb}_2\text{S}_3$ ) has much attraction as light harvesting material in solar cell applications.  $\text{Sb}_2\text{S}_3$  solar cells are reported with a dense blocking layer and mesoscopic  $\text{TiO}_2$  scaffold. But still, in both cases, the performance of  $\text{Sb}_2\text{S}_3$  solar cells are unsatisfactory. However, planner  $\text{Sb}_2\text{S}_3$  solar cells would be more competitive because it is simpler and has a higher open circuit voltage due to reduced charge carrier recombination. Herein, planner  $\text{Sb}_2\text{S}_3$  solar cells have been successfully made using spin coated  $\text{Sb}_2\text{S}_3$  as the absorber, dense blocking  $\text{TiO}_2$  (bl- $\text{TiO}_2$ ) as the electron conductor and poly (3-hexathiophene) (P3HT) as the hole conductor. This study pinpointed the dependence of cell performance on the thickness of the blocking  $\text{TiO}_2$  layer. The bl- $\text{TiO}_2$  was deposited by spin coating at rpm with a different number of spin coat cycles (1-5). The  $\text{TiO}_2$  precursor solution was prepared by mixing of Titanium IsoPropoxide (TIIP), of butol-1-ol and of diethanolamine. The blocking properties and thickness variation of the bl- $\text{TiO}_2$  layers fabricated with a various number of spinning cycles were verified by cyclic voltammograms and UV-Vis spectra respectively. The optimization of the  $\text{TiO}_2$  blocking layer to enhance the device performance was carried out on the planner device consisting of FTO/bl- $\text{TiO}_2$ / $\text{Sb}_2\text{S}_3$ /P3HT/Ag and the optimized device with of bl- $\text{TiO}_2$  exhibited the power conversion efficiency of at 1 sun illumination.

**Keywords:** Blocking  $\text{TiO}_2$ , Planner structure, Performance,  $\text{Sb}_2\text{S}_3$ , and Spin coat cycle

**Acknowledgment:** *This work was financially supported by the National Research Council (NRC) (Grant No 18-005)*