

Microbial cellulases: An overview and applications (ID: 173627)

Microbial cellulases: An overview and applications

S.K.Jayasekara¹ and R.R.Ratnayake^{1*}

¹National Institute of Fundamental Studies, Kandy, Sri Lanka

*renukar@ifs.ac.lk

Abstract

Cellulases are a complex group of enzymes which are secreted by a broad range of microorganisms including fungi, bacteria and actinomycetes. In the natural environment, synergistic interactions among cellulolytic microorganisms play an important role in the hydrolysis of lignocellulosic polymer materials. In fact, it is the combined action of three major enzymes which determines the efficiency of this process. They are exoglucanases, endoglucanases and β -glucosidase. Microorganisms produce these enzymes in a diverse nature which determines their efficiency in cellulose hydrolysis. During the cellulose degradation reaction, the enzyme targets the β -1, 4-linkages in its polymeric structure. This is an essential ecological process as it recycles cellulose in the biosphere. The application of this same scenario for industrial purposes is identified as an emerging area of research. Biofuel production, textile polishing and finishing, paper and pulp industry and life style agriculture are among the key areas where cellulase enzyme shows a broader potential. The objective of this chapter is to discuss the structure, function, possible applications as well as novel biotechnological trends of cellulase enzymes. Furthermore, it will be discussing possible low cost, enzymatic pretreatment methods of lignocellulosic material in order to use it as an efficient raw material for biofuel production.

Keywords: Applications of cellulases, Cellulase activity, cellulose, cellulolytic microorganisms, industrial applications of cellulase, pretreatment of cellulose

1. Introduction

Biomolecules derived from natural resources are playing a major role in manufacturing products needed for daily use. Enzymes are one of those molecules that are globally recognized for their multifarious applications in industries. For instance, their utility in brewing and wine making, dairy products, detergent manufacturing, food and feed, pharmaceutical production, paper and pulp industry is huge. One of those most widely used enzymes all over the world is cellulase. According to recent global cellulase market analysis reports, the demand for this enzyme is exponentially increasing.

Cellulose, the substrate of cellulase is the most abundant polysaccharide present on earth. It is the main substance in plant materials. Anselme Payne was the very first person to discover and isolate this amazing compound from green plants [1]. It happened more than two centuries ago. From the past, cellulosic materials have played a crucial role in daily human life. They used it to fertilize their soil for



crop cultivation. It was also fodder for their cattle. It was firewood for cooking and they were igniting cellulosic material to generate heat whenever they needed to produce energy.

Currently, the role played by cellulose is not that simple. Especially, as it is recognized as a cost-effective raw material, the useful applications of cellulose in industrial sector have become much more complex. This has laid a huge platform for scientists to do cellulose-based research in multidisciplinary approaches. One such area is hydrolysis of cellulose. In nature, this is usually accomplished by cellulases. Cellulase is catalyzing hydrolysis of cellulose.

However, cellulase is not a single enzyme. It is a group of enzymes which is mainly comprised of endoglucanase, exoglucanases including cellobiohydrolases and β -glucosidase. Fungi, bacteria and actinomycetes are recorded to be efficient cellulase enzyme producers in the natural environment. These microorganisms must secrete the cellulases that are either free or cell-surface-bound. Their enzyme production efficiency and the enzyme complex composition are always diverse from each other. Although, both aerobic and anaerobic microorganisms produce these enzymes, aerobic cellulolytic fungi *viz: Trichoderma viridae, T. reesei* are excessively studied. The enzyme breaks β -1, 4-linkages in cellulose polymer to release sugar sub units such as glucose. This notion is applied in industries either cellulose is utilized as a raw material or cellulose degradation is a must.

According to recent enzyme market reports, the key areas of the industry where cellulase enzyme is increasingly being applied are healthcare, textile, pulp and paper, detergent, food and beverages. Its wide application in coffee processing, wine making and fruit juice production are related to food and beverage segment. In other industrial applications, it is broadly used to produce laundry detergents, cleaning and washing agents. Cellulase is also being highly recognized as an effective alternative to available antibiotics for treatment of biofilms produced by *Pseudomonas*. Therefore, potential of cellulases to fight against antibiotic resistant bacteria is an amazing trend which will overcome problems in healthcare sector [2].

Application of microorganisms or microbial enzymes for pretreatment of lignocellulosic material is currently earning a huge attention of the industry. This is a result of growing interest about depletion of fossil fuel resources in the world which have inspired the production of bioethanol from lignocellulosic biomass through enzymatic hydrolysis [3]. Ligno- cellulosic biomass is one of the best options as a low cost, readily available, eco-friendly raw material. However, it is not found alone. Cellulose is forming lignocellulose in combination with hemicellulose and lignin which finally becomes a compact network structure [4]. Moreover; it has a crystalline structure which is hard to break down. Therefore, cellulose is insoluble in water and causes limitations in hydrolysis. That is why it is essential to pretreat lignocellulosic material in industries like bioethanol production. During pretreatment, it will loosen up the crystalline structure and facilitate the degradability to release fermentable sugar forms. There are several methods available for pretreatment of lignocellulose. *viz:* Physical, chemical and biological methods. Biological pretreatment using cellulolytic microorganisms and their enzymes are found to be the best way of addressing this problem.

By all means, cellulase is an enzyme which can cause a huge economic impact. However, there are some considerable bottlenecks of utilizing this enzyme in industry. For examples; the higher cost of cellulase and less catalytic efficiency



are especially understood. Another important point is less understanding of the relationship between hydrolysis mechanisms and molecular structure of the enzyme. This knowledge is important to carry out further improvements in the enzyme to enhance its catalytic activity. Therefore, this chapter is discussing about the structure and function of cellulase in order to understand its mechanisms of action. The details on current applications of the enzyme have also been summarized here. Furthermore, the efforts have been taken to bring together information on novel biotechnological trends of cellulase. Moreover, it is discussing about possible low cost, enzymatic pretreatment methods that have practiced for lignocellulosic material in order to use it as an efficient raw material to produce bioethanol.

2. Cellulose

Before moving on to cellulase, it is essential to understand cellulose which is the substrate of cellulase enzyme. This section will provide a short description about cellulose.

2.1 Cellulose is a polysaccharide

3

Cellulose is a linear homopolymer composed of D-glucopyranose units linked by β -1,4-glycosidic bonds. It mainly contains carbon (44.44 %), hydrogen (6.17 %) and oxygen (49.39 %). The chemical formula of cellulose is $(C_6H_{10}O_5)_n$; n , called the degree of polymerization (DP), represents the number of glucose groups, ranging from hundreds to thousands or even tens of thousands. In the twentieth century, it was proved that cellulose consists of pure dehydrated repeating units of D-glucoses, and the repeating unit of the cellulose is called cellobiose. Cellulose is a linear polymer composed of β -1, 4- linkages among glucose monomers [5]. Usually a cellulose chain is formed by polymerization of more than 3000 monomer subunits. In other words, this polymer is made by β -(1 \rightarrow 4)-D-glucopyranose units in 4C_1 conformation. It consists of long chains of anhydro-D-glucopyranose units (AGU) with each cellulose molecule having three hydroxyl groups per AGU with the exception of the terminal ends. Cellulose has both crystalline and amorphous regions in its structure in various proportions [5]. Those regions are intertwined to form the structure of cellulose. There are four major crystalline forms. For instance, I α , I β , II and III. This crystalline structure is a result of intra-molecular and inter-molecular hydrogen bonding between glucose monomers in cellulose. These hydrogen bonds construct a huge network that directly contributes the compact crystal structure of cellulose polymer. On the other hand these strong intra-molecular and inter-molecular hydrogen bond formation leads to poor solubility of cellulose.

2.3 organization of cellulose

In plant cell walls, cellulose exists as different levels of structures, i.e., single cellulose chains, elementary fibrils (consisting of tens of single cellulose chains),



microfibrils (bundles of elementary fibrils) and cellulose propose that the macrofibril is formed by a number of newly synthesized elementary fibrils. As the cell grows, the macrofibrils may split to form individual microfibrils consisting of a single elementary fibril associated with non-cellulosic polymers like hemicelluloses. In other words, elementary fibrils and macrofibrils contain only cellulose while the microfibrils contain both cellulose and non-cellulosic polymers. It is noted that others consider a microfibril as consisting of a number of elementary fibrils. Microfibril is an elementary fibril associated with non-cellulosic polymers. Each microfibril might contain up to 40 cellulose chains and is about ~10-20nm in diameter. Many such cellulose chains aggregate into bundles called micelles and micelles ² into microfibrils. Micelles are interconnected with few cellulose fibers. These fibrils are then cross linked by hemicellulose and pectin matrixes to form macro fibrils which have the function to mediate structural stability in the plant cell wall. The spaces between cellulose and pectin matrixes are filled with lignin which covalently links to hemicellulose, providing mechanical strength to the plant cell wall. This structure which present in plants is collectively called lignocellulose. Other components known as extractives including fats, phenolic, resins, and minerals are also present in lignocellulosic biomass.

3. Cellulase

3.1 Global demands for enzymes

Enzymes are known to be very useful in many industrial processes. Their broad applicability has created a significant market demand in the recent years. According to market reports on world enzyme demand 2017, they have recognized several key factors which lead to huge consumer demand for enzymes. Some of them are completely bound with economical advances. For example, increased per capita income in developing countries causes huge growth in consumer-related industrial applications [6]. A recent industry study done by Freedonia in January 2018 on “Global Industrial Enzymes” reveals that global demand for industrial enzymes is projected to grow 4.0% per year to \$5.0 billion in 2021. This report also emphasizes the gains in personal incomes in developing countries as the key factor which is supporting growth in demand for enzymes. When it is coming to developments in scientific research, especially in biotechnology, molecular biology and genetics, have already laid a strong platform to work on enzymes. Continued advances in these areas of research, particularly related to DNA manipulation and sequencing, result in extensive increases in enzyme demand worldwide. Cellulase is one such enzyme which earns consecutively increasing demand. Therefore, collection of knowledge about this enzyme is essential for further development of fundamental and applied research on cellulase and for consequent application in human life.

3.2 Molecular structure and function of cellulase

3.2.1 Molecular structure of cellulase

It is produced by fungi, bacteria, actinomycetes, protozoans, plants, and animals. According to Carbohydrate-Active Enzymes database, there is information of the



glycoside hydrolase (EC 3.2.1.-) families. Glycoside hydrolases, including cellulase, have been classified into 115 families based on amino acid sequence similarities and crystal structures. A large number of cellulase genes have now been cloned and characterized. They are found in 13 different families. Furthermore, there are 3D structures of more than 50 cellulases. All of cellulases cleave β -1, 4-glucosidic bonds. However, they display a variety of topologies ranging from all β -sheet proteins to β / α -barrels to all α -helical protein.

In the structure of cellulase, there are catalytic modules and non-catalytic modules. The catalytic modules of cellulases have been classified into numerous families based on their amino acid sequences and crystal structures. The non-catalytic carbohydrate-binding modules (CBM s) and/or other functionally known or unknown modules may be located at the N- or C-terminus of a catalytic module. Usually, fungal and bacterial cellulase mainly has two or more structural and functional domains. Both aerobic as well as anaerobic microorganisms are producing this enzyme. Therefore, there are two types of cellulase systems: noncomplex and complexed. A noncomplex cellulase system is produced by aerobic cellulolytic microorganisms and it is a mixture of extracellular cooperative enzymes. In a non complexed cellulase system, the common arrangement is joining of a catalytic domain with a cellulose binding domain (CBD). A complexed cellulase system is produced by anaerobic microorganisms and it is called a "cellulosome." Cellulosome is assembled by joining a catalytic domain with a dockerin domain. The enzyme is a multiprotein complex anchored on the surface of the bacterium by non-catalytic proteins that serves to function like the individual noncomplex cellulases, but is in one unit.

In addition to these two major domains in the cellulase structure, there are some other domains that are present in many cellulases. For instance, S-layer homologous (SLH) domain, Fibronectin- type 111 domains, NodB-like domain and there are also other regions of unknown function. These domains are often connected by Pro and Hydroxy amino acids (Threonine & Serine) enriched linker sequences. Among all these domains, catalytic and cellulose binding domains are the most important because they are the domains which considered participating in hydrolytic mechanisms of the enzyme.

3.2.2. Catalytic function of cellulase enzyme

Cellulase catalyzes the decomposition of cellulose polysaccharide by simply breaking down β -1,4-glycosidic bonds. Three major types of enzymes are generally involved in hydrolyzing cellulose micro fibrils in plant cell wall: endoglucanase, exo glucanase and β -glucosidase. Complete cellulose hydrolysis is mediated by a combination of three main types of cellulases. Endoglucanases, e.g., 1,4- β -D-glucan-4-glucanhydrolase could randomly attack the internal bonds at amorphous regions of cellulose while creating new chain ends that can be attacked by other types of enzymes. It is generally believed to be very active against soluble cellulose derivatives or acid-swollen amorphous cellulose. Exoglucanase, e.g., 1,4- β -Dglucan-cellobiohydrolases, generates glucose or cellobiose from the reducing or non-reducing end of cellulose polysaccharide chains. Unlike endoglucanase, exoglucanase is normally very active against crystalline cellulosic substrate such as Avicel or celooligosaccharides. Finally, β -glucosidase, e.g., β -glucosideglucohydrolases, can hydrolyze cellobiose to glucose from the nonreducing ends and it is inactive against amorphous or crystalline cellulose. Although an exact mechanism is not yet finalized, fragmentation of cellulose aggregations into short fibers has been observed and reported during



the beginning of cellulose hydrolysis prior to releasing any detectable amount of reducing sugars. This is known as known as amorphogenesis.

There are two catalytic mechanisms of cellulases. They simply introduced as retaining mechanisms and inverting mechanisms. Cellulases cleave glucosidic bonds by using acid–base catalysis. The hydrolysis is performed by two catalytic 4 residues of the enzyme: a general acid (proton donor) and a nucleophile/base. Depending on the spatial position of these catalytic residues, hydrolysis occurs via retention or inversion of the anomeric configuration. For “retaining” cellulases, the anomeric C bearing the target glucosidic bond retains the same (substituent) configuration after a double-displacement hydrolysis with two key glycosylation/deglycosylation steps. By contrast, for “inverting” cellulases, the anomeric C invert its (substituent) configuration after a single nucleophilic displacement hydrolysis [7].

4. Applications of microbial cellulases

Microbial cellulases are biomolecules derived from diverse groups of microorganisms including bacteria and fungi. For many decades, these enzymes have played a crucial role as biocatalysts in human life. They have shown their potential application in large number of industries. Especially there is a huge market established for specific biotechnological approaches based on this enzyme. Textile, paper & pulp, laundry & detergent, agriculture, medicine and food & feed are some of the major industries which employ microbial cellulases. According to Coherent Market Insights, Textile industry is the dominant market for cellulases in 2017. According to most of the enzyme market research reports published in 2018, Food & Beverages, Textile Industry, Animal Feed and Biofuels have been reported to be the major areas of applications.

According to another Global Cellulase (CAS 9012-54-8) Market Research Report published in 2018, Asia-Pacific is the largest consumer of Cellulase, with a revenue market share nearly 32.84% by 2016. Furthermore, report data showed that 29.71% of the Cellulase market demand in Animal Feed, 26.37% in Food & Beverages, and 13.77% in Textile Industry in 2016. This same report forecasts that the applications of cellulases will reach 2300 million US\$ by the end of 2025, growing at a CAGR (Compound Annual Growth Rate) of 5.5% during 2018-2025 period. These data suggests that the application of cellulases in industries is drastically rising annually. Novozymes and Dupont from Denmark are key cellulase enzyme producers supplying these enzymes to the global market for industrial applications. From this point forward, in this chapter, our major effort was to discuss about the current applications of cellulases in major fields that have listed above. The novel biotechnological trends emerging in those fields while understanding the key areas of research where further studies required also surfaced to an extent.

4.1. Textile industry

Textile is one of the largest industries in the world. The customer demand for fashion is increasing as they want uniqueness in styles, colours and the clothes they wear. There was a significant growth in this industry during last few decades as a result of this increasing customer demand. This enzyme has now become the third largest group of enzymes used in these applications [8]. This creates a very competitive market platform for manufacturers that they are always looking



for environmental friendly approaches of giving their products a unique look. Cellulase is used for many purposes in the industrial sector.

Especially for textile wet processing. Biostoning of denim fabric, biopolishing of textile fibers, softening of garments and removal of excess dye from the fabrics are some of the major applications of this enzyme in the industry. Fungal cellulases from *Trichoderma reesei* are the mostly applied enzyme in textile industry. Apart from that, Actinomycetes from the genera *Streptomyces* and *Thermobifida* and other genera of bacteria, such as *Pseudomonas* and *Sphingomonas*, are some of the sources of enzymes to be used for decolourisation and degradation of textile dyes [9].

Bio-stoning and bio-polishing are well-known for the best applications of cellulases in the current textile industry.

4.1.1. Bio-stone washing

The conventional washing process of denim is usually a three step process. The denim fabric is first treated with amylase enzyme to remove the starch coating of the fabric. This process is called desizing. During this process, starch is broken down into maltose which is a water soluble disaccharide composed of 2 glucose molecules. Then the fabric is given treatment by providing abrasion to the material in pumice stones added washing machine. This wash was completely achieved by adding chemicals like sodium hypochlorite or potassium permanganate. This traditional process has several disadvantages. The addition of pumice stones must be done in larger quantities. This was affecting the machine's productivity in an adverse way causing tear effects. After the wash is completed, the manual removal of stones is needed. This is causing further reduction of the process's efficiency. Environmental pollution as well as huge amount of backstaining caused. The backstaining is the reaction by which the removed dye molecules are deposited on the denim fabric again.

Application of microbial cellulases was found to be an efficient alternative for pumice stone washing. It was first staged in 1980's. Use of stones is currently replaced by cellulases in a successful way. During this process, cellulases act on the denim fabric which is made of tough cotton. The indigo dye which is used to colour the fabric is trapped inside the cellulose fiber in this cotton material. Usually, the indigo dye is mostly attached to the surface of the yarn and to the most exterior short cotton fibres. When the fabric is treated with the enzyme; it hydrolyzes and breaks small fibers coming out of the fabric which loosens the dye. For this purpose, the β -1, 4-linkages of cellulose chains will be broken down and simple water soluble sugars will be formed. This will remove the fibers which traps indigo dye. Then the dye is easily removed from the fabric giving a faded look.

Trichoderma reesei acidic endoglucanase II has been found to be very efficient candidate for Biostoning [10]. The neutral cellulase enzyme extracted from *Humicola insolens* is also reported to be commonly applied in this process [11]. The use of cellulases has several advantages over stone washing with pumice stones including high productivity, less work intensive, safer environment, short treatment times, less wear and tear of machines. Currently, denim with a worn out look has a huge demand in the textile market.

The major disadvantage associated with the application of microbial cellulases is again the backstaining. The redistribution of dye on the fabric covers up the shaded look given by the treatment. In order to overcome this problem, several biotechnological approaches have been already experimented by researchers. Immobilization of cellulases on pumice stones is one such cost-effective way of



doing this. It has also been observed that acidic endoglucanase causes a better abrasion and less back staining compared to neutral endoglucanase. For example the cellulase given by *Trichoderma reesei* is more efficient in preventing backstaining as compared to neutral endoglucanase of *H. insolens*.

The latest trend of biostone washing is to utilize an enzyme mixture composed of Amylase, Cellulase and laccase [12]. The sizing is the process by which denim material surface is covered by a compound like starch to provide rigid and stiffness to raw denim, provide strength and friction resistance during handling. During washing, this surface layer of starch must be removed first to facilitate interaction between cellulases and cotton fibers. The amylase hydrolyses starch from the fabric and causes de-sizing. Cellulase hydrolyses small cellulose fibers and laccase usually causes bleaching of the fabric. Laccases (EC 1.10.3.2) with intrinsic electron-donating tendency can decompose indigo in the solution as well as on the fabric creating bleaching effect on denim garments. The indigo dye is converted into Isatin and Anthranilic acid like chemical forms. This prevents backstaining of dye on the fabric surface. Eventually this will give a complete faded look to the denim fabric. The purpose of using a mixture is to improve the efficiency of biostone washing process by allowing those three enzymes to work together in a sequential manner.

In a recent study, it is reported that an alkali stable cellulase in combination with xylanase from *Thermomonospora sp.* has a reduced tendency of backstaining [13]. However, the effluents generated during biostone washing must be pretreated to remove dye material and the intermediate chemical compounds present after the reaction. Otherwise, these dyes might pollute natural waterways, and soil. Most of these dye residues are toxic and carcinogens that would cause adverse health effects in human and animals. Although, biodegradability of enzymes is a positive advantage here although chemical by products formed during dye removal must be neutralized.

4.1.2. Bio-polishing

Cellulosic fibrous materials like cotton and linen are always losing appearance because of fuzz formation on the fabric surface. Fuzz is occurred due to short fibers protruding out from the surface of the fabric. Fuzz is sometimes loosely attached to the fabric forming a ball-like appearance which gives an unattractive look to the fabric. This is called pilling.

It is found that cellulase preparations rich with endoglucanase are the best for biopolishing. It is a finishing process which increases the quality of the fabric by reducing surface fuzziness and pilling property of cellulosic fibre. The process basically aims on removing micro fibrils of cotton through the action of cellulase enzyme. It enhances fabric look, hand feel and colour by giving a smooth and a glossy appearance. This is also leading to improve colour brightness; hydrophilicity and moisture absorbance by the fabric [13]. The acidic cellulases produced by *T.reesei* and *Aspergillus niger* are found to be enormously effective in this process. The bio-polishing is ecofriendly because the enzymes used in this process are readily biodegradable and non-toxic.

4.1.3. Bio finishing

This task is also efficiently done by endoglucanase –rich cellulase mixtures. The repeated washing of a cotton garment makes it fluffy and dull. This is due to partially removed microfibrils on the fabric surface. The enzyme can remove



these fibrils and give back the smooth surface and original colour to the fabric. This will also give a soft hand feel to the material and also this is a good way of removing stains and dirt spots that are trapped within the cotton fiber network [14, 15]. This is simply a similar process to bio-finishing.

4.1.4. Bio scouring

This is the process that removes non cellulosic material from the surface of the cotton. This is usually done with cellulase alone or in combination with other enzymes such as pectinase. Pectinase digest the pectin substance present among cellulose fibers. This helps to remove the intact connection between cuticle and the main body of the cellulose fiber. This helps to degrade the primary cellulosic wall of the fiber. The ultimate result is the destruction of the cuticle [16]. This reaction increases the softness of the fabric.

4.1.5. Bio-carbonization and Wool Scouring

This is kind of a biological mode of cleaning the fabric from the cellulosic or vegetative impurities with the help of enzymes. When a pure cotton or cotton blend fabric is prepared, some traces of unwanted cellulosic material still may remain in the fabric. They may result in imperfect finishing and lower quality of the fabric. Earliest methods of carbonization involved application of sulfuric acid. It was not only expensive but also corrosive, unsafe and hazardous. Being a non-hazardous, non-corrosive and eco-friendly method, enzymatic carbonization was a promising alternative. This method was perfect for removal of cellulosic impurities from the material because as it was least affecting the colour and the hand feel of the fabric. The removal of vegetative impurities from the surface of raw wool using cellulases is called wool scouring [17]. Cellulases can be used alone or in combination with other enzymes such as pectinases to increase the efficiency of this process. These methods are doing less damage to the fabric when compared to treatment with sulphuric acid.

4.1.6 De-fibrillation of lyocell

Lyocell is the generic name for a biodegradable fabric that's made out of treated [wood pulp](#). This material is used in everything from clothing to cars. This is obtained from wood pulp using a solvent spinning method. The solvent system which is usually applied is an organic compound called [N-methylmorpholine N-oxide](#). Some main characteristics of lyocell fibers are that they are soft, absorbent, and very strong when wet or dry, and resistant to wrinkles. Lyocell fabric can be machine washed or dry cleaned and can be dyed many colors. One chief defect of this material is fibrillation. This is the formation of small tangled fibrils on the surface of the fabric. Cellulases can be efficiently applied to remove these fibrils and give the fabric an increased softness and an improved appearance. This is also good for preventing fuzz and pill formation.

The underlying mechanism of Bio-polishing, bio-finishing, bio-scouring and bio-carbonization and de-fibrillation of textile is same. It is the removal of cellulosic fibers and impurities from the fabric in order to give the fabric a smoother, softer and a brighter final touch. Although the applied enzymes are



non-toxic and readily biodegradable, the final effluent produced will show increased Biological Oxygen Demand (BOD), Chemical Oxygen Demand (COD), Total Dissolved Solids (TDS) and Total suspended solids (TSS) to a certain extent because the effluent may contain digested sugar and cellulosic forms. Direct release of this effluent to natural water bodies may cause water pollution. Alkalinity and P^H fluctuations of the effluent will also result in polluted water which is not good for human and animal consumption. This may cause health issues like skin irritations in humans. On the other hand, the enzymatic treatments need an incubation period to facilitate the reaction between enzyme and fabric. As this is a fermentation reaction this may release certain odors to the environment which may cause air pollution to a certain extent. Moreover, textile dyes are removed during textile processing. Most of the dyes are toxic and some are highly carcinogenic. Mixing this type of dyes with water is definitely causing adverse health effects in humans. Therefore, direct release of effluent without applying any pretreatments to neutralize these toxic compounds will breach the stability in ecosystems to which they are released. Therefore, establishment of pretreatment facilities and water quality testing procedures are essential for these enzymatic textile processing plants.

Lyocell production has a different impact on environment than the other textile polishing and finishing processes. The solvent which is used to manufacture this textile is N-methylmorpholine N-oxide. This is usually causing acute toxicity (oral, dermal, inhalation), skin irritation, serious eye damage & irritation, skin sensitization and specific target organ toxicity. These are also hazardous to aquatic environments. These possible environmental impacts must be always addressed although application of enzymes in textile processing is ecofriendly.

4.2. Paper and pulp industry

This is one of the largest industrial sectors in the world. According to World Wildlife Fund (WWF), the pulp and paper industry, which includes products such as office and catalog paper, glossy paper, tissue and paper-based packaging, uses over 40 percent of all industrial wood traded globally [18]. On the other hand latest paper industry statistics reveal that world's three largest paper producing countries are to be China, the United States, and Japan. These three countries account for half of the world's total paper production, while the leading paper importing and exporting countries are Germany and the United States [19]. United States is reported to be the largest consumer of papers.

All these statistics are reflecting the huge role played by this industry in the global market. Papers and pulp are renewable resources. Therefore, recycling and reusing are two popular concepts related to this industry. Application of microbial cellulases is usually utilized for this purpose. The application of cellulases in this industry is broader. Starting from 1980s up to now the possible applications are branching towards many areas. For instance, deinking, pulping, bioremediation of industry wastes, bleaching and fiber enhancement can be taken.

4.2.1. Pulping

The drawbacks in mechanical pulping processes of woody raw materials such as refining and grinding resulted in pulps with higher amounts of fines, bulk and stiffness. On the other hand the process was high energy consuming which



was not a profitable option for an industry. Meanwhile, bio-pulping using enzymes such as cellulases is an energy saving way and also it is eco -friendly [20]. The substantial energy saving is reported around 20-40% While in contrast, biomechanical pulping using cellulases resulted in substantial energy savings (20–40%). During the refining process, it generates small particles of the pulps. These particles reduce the drainage rate during the paper making process. These particles can be readily degraded by cellulases in order to increase the drainage ability of the pulp. Mixtures of cellulases (endoglucanases I and II) and hemicellulases have also been used for bio modification of coarse pulp material to improve fiber properties. It is strengthening the hand sheets. On the other hand biological pulping has the potential to improve the quality of pulp, properties of paper while reducing energy costs and environmental impact [21].

4.2.2. Deinking

In traditional deinking, large quantities of chemicals are used which makes the method expensive, environmentally damaging and increases the release of contaminants [22]. The main advantage of bio-deinking is the ability of avoiding the alkali use during the process. This prevents yellowing of the paper. Cellulases alone, or used in combination with xylanase, are beneficial for deinking of different types of paper wastes. In most of the applications, partial hydrolysis of carbohydrate molecules releases ink from the fiber surface. This is done by a mixture of cellulases alone or in combination of cellulase and hemicellulases. It has been postulated that improvements in dewatering and deinking of various pulps result in the peeling of the individual fibrils and bundles, which have high affinity for the surrounding water and ink particles. The advantages associated with enzymatic de-inking are clean look of paper, enhanced brightness as well as environmental pollution reduction

4.2.3. Bio-modification and Bio-characterization of Fibers

Successful application of cellulases and hemicellulases mixtures has been reported to modify properties of fibers. Usually in paper industry the making of paper is made easier by improving the beatability, runnability and drainage of paper pulp during the process. Modifications of fiber properties are also achieved through treatment of paper by cellulase enzyme [20]. Not only that but also the enzymatic hydrolysis helps in characterization of fiber using various techniques such as scanning electron microscopy (SEM) and HPLC [23].

4.3. Laundry and Detergent Industry

When it is coming to detergent industry, the application of enzymes in manufacturing enzymatic washing agents or biological detergents, dates back to 1960s. Using enzymes in detergent formulae is a common practice today. In fact, according to market reports, by 2014, the detergent industry was the largest single market for enzymes at about 25 - 30% of total sales [22]. Another market research report published in 2017 on laundry detergent market stated that its global market size valued at USD 133.3 billion in 2013. This gives an idea about the current hugeness of the global detergent market. Huge amounts of alkaline enzymes are used in the detergent industry, and they have been widely



incorporated into heavy-duty laundry and automatic dishwashing detergents. The alkaline enzymes broadly used in modern detergents are protease, cellulase, α -amylase, lipase, and mannanase.

The capability of enzymes to remove stains is the major focus of using them in manufacturing detergents. Cellulases are available in the market in different brands. For instance, Celluzyme® and Carezyme® are two main brands applied in detergent blends. These detergent blends are mainly applied in washing fabrics made of cotton and cotton blends. These detergents are making fiber modifications in the fabric in order to improve colour brightness, softness and particulate soil removal.

The repeated washing of a garment made of cotton or cotton blends tends to get a 'fluffy' look and the colours become duller. This effect is due to partial detachment of microfibrils present on the fabric surface. Cellulases present in the detergent can result in the removal of these microfibrils thereby increasing the smoothness of the surface and restoring the original colour of the garment. Enhancement of softness of the fabric is an added advantage of fabric treatment with detergents containing cellulases. Cellulases extracted from fungi like *Trichoderma* sp (*T. longibrachiatum*, *T. reesei*, *T. viridae*, and *T. harzianum*), *Aspergillus niger*, *Humicola* (*H. insolens* and *H. griseothermoidea*) and *Bacillus* [1] have been extensively studied so far for application in detergents. However, alkaline cellulases are considered as most potential industrial candidates to be used as additives to conventional detergent ingredients due to their ability to remove soil and dirt particles present in the interfibril spaces. Recently, liquid laundry detergents have been used to increase the stability of cellulases. The liquid detergent comprises various components including an anionic or non-anionic surfactant, protease, cellulase, citric acid or water soluble salt, a mixture of propanediol, and boric acid or its derivatives. The composition of the detergent was achieved by first adding diol and boric acid followed by addition of citric acid/salt, as the order of addition is important to enhance the stability of cellulases. The cellulases remove the rough protuberances or cellulose aggregates still attached to the fabric and result in a glossier smoother look of the fabric [23].

Most recent innovation is to use combinations of enzymes in detergents. Cellulases are used in combination with other enzymes like proteases and lipases. The combination of enzymes is used to increase efficiency on stain cleaning and fabric care. For instance, SaniZyme® is a 4 enzyme liquid detergent containing Lipase, cellulase, Amylase and Protease. This is a bacteriostatic enzymatic detergent for the removal of blood, protein, mucous, fats, lipids and carbohydrates from all types of endoscopic equipment and surgical instruments. Another example is Getinge Clean MIS Detergent® which is also a formulation which includes protease, lipase, amylase and cellulase enzymes, surfactants, sequestering agents and corrosion inhibitors (typical pH in use dilution 8) which is specifically designed to clean complex, minimal invasive instrumentation. Furthermore, detergents are recently coming in different forms simple granulated powders, liquids and gels. The consumer demands have always expanded the scope of product novelty. As a result of that nowadays detergents are coming to the market in different colors, fragrances and in easy to use formulae.

4.4 Agriculture

The application of cellulases in agriculture is usually reported in enhancement of crop growth and a control agent of plant diseases. For this purpose, combinations of cellulases, hemicellulases and pectinases broadly applied.



Certain fungal cellulases are with the ability to degrade cell wall of plant pathogens. There are lots of details about application of bacteria such as Plant Growth Promoting Rhizobacteria (PGPRs) to improve plant performance. It is reported that these bacteria play a major role in reducing application of chemical fertilizers increasing plant development and also, controlling potential plant pathogens and protecting plants from diseases. Moreover, many fungi including *Trichoderma* sp., *Geocladium* sp., *Chaetomium* sp., and *Penicillium* sp enhance seed germination, rapid plant growth, flowering, improved root system and increased crop yield. However, exact mechanisms behind these reactions are not yet clearly understood. But all these organisms have the ability to produce cellulase and related enzymes which may have a direct participation in these reactions. Some reports are there about possible synergisms between bacterial cellulase production and bacterial antibiotic production against plant pathogenic fungi.

According to available information, it is evident that cellulolytic microorganisms are participating in many processes viz; rhizosphere soil decomposition, increasing the availability of nutrient for the plant, controlling plant pathogens, facilitating root colonization and penetration of cereal crops improving yields and nutritional contents. However, as there are no solid evidence to prove the mechanisms behind these, this area needs further research. The studies should be performed in order to characterize and improve applications of microbial cellulases in this field.

During traditional agriculture practices, especially in countries like Sri Lanka, farmers used to add straw, Gliricidia leaves like cellulosic materials into their fields. They observed that the incorporation of these types of plant material not only improved the quality of the soil but also increase the yield due to added nutrients. Therefore, it is obvious that in this type of processes cellulolytic microorganisms must have a direct contribution.

4.5 Medical applications

Pharmacology and medicine is currently a very active field of research that novel discoveries are coming into action. One such area is cellulases for development of medicine. By the way, humans are not cellulase producers but recent research on health and medicine reveals the benefits of consuming blends of enzymes including cellulase. As a result of global demand for enzyme blends, cellulase produced by the natural fermentation process of *Trichoderma reesei* and *Bacillus licheniformis* has been included in commercially available enzyme blends. This type of enzyme blends target collective digestion of cellulose rich fibrous substances such as fruits and vegetables, cereals, legumes, bran, nuts and seeds, soy, dairy, healthy greens, sprouts, and herbs along with fats (lipids), sugars, proteins, carbohydrates, and gluten. one such example is [VeganZyme®](#). Apart from that digestive aids (e.g., Digestin, P-A-L Plus Enzymes, Polyzyme Plus, etc.) to treat people suffering from metabolic disorders is evolving as a promising strategy in medicine.

In some records, the direct and indirect applications of cellulase in medicine have been mentioned apart from using it as consumable enzyme blends.

4.5.1 Indirect applications of cellulases for medical purposes



Cellulase of fungal origin in combination with chitinases and lysozymes has a reported use in chitosan degradation. To obtain chitosan, a partial degradation of chitin must take place. As cellulose, chitin is a structural polysaccharide present in animals such as marine animals like shrimp, insect exoskeleton as well as participates in the formation of some parts of fungal cell walls. Chitin is a poly- β -1, 4-N-acetyl-D-glucosamine, conforming crystalline microfibrils. This polysaccharide provides structural integrity, stability and protection to animals. Chitosan is the most important semi crystalline derivative form of chitin. This is obtained by partial deacetylation of chitin (around 50%, soluble in aqueous solution) under alkaline conditions or enzyme hydrolysis. Chitosan and its derivatives have many medical applications *viz*: surgical sutures, bone rebuilding, production of artificial skin, anticoagulant, antibacterial agent, hemostatic dressings, anticancer and anti-diabetic agents (in combination with metals), hypocholesterolemic effectors, elaboration of cosmetics, and production of biopharmaceutics and encapsulation of diverse materials [24, 25].

Apart from these applications, a lot of reports have been published on several studies reporting how cellulases hydrolyze chitosan and their potential biomedical effects. The antitumor activity of cellulase- treated chitosan [26] and antimicrobial activity of Low Molecular Weight Chitosan obtained by *Trichoderma* commercial enzymes are some of the areas. However, the lack of solid evidence is a common issue on this area. Therefore, this is also an area of research where further studies are needed to clarify the applications of cellulases.

4.5.2 Direct applications of cellulases for medical purposes

A bezoar is a mass found trapped in the gastrointestinal system. Phytobezoars, as its name suggests, are composed of indigestible plant material (e.g., cellulose). In other words, it is a gastric concretion formed of vegetable fibers, seeds and skins of fruits and sometimes starch granules and fat globules trapped inside gastrointestinal tract. This is a common problem frequently reported in patients with impaired digestion and decreased gastric motility. Although sometimes surgeries are needed to remove these stagnated substances, certain minor conditions can be treated by cellulases. The common application reported is fungal cellulases. As there are no much reports about application of bacterial cellulases, research can be conducted to find out the application of potential cellulolytic bacterial cellulases to treat this condition. However, what is most important is any of these individual enzymes or enzyme cocktails should not adversely affect the healthy body cells.

Another possible direct application of cellulase in medicine is degradation of cell walls of pathogenic organisms. *Acanthamoeba* is a Protista which causes a very rare as well as serious corneal infection which leads to blindness. This is simply called Keratitis. This amoebic keratitis is an acute sight-threatening corneal infection associated with contact lens misuse [27]. This organism has two stages in its life cycle. The cyst and trophozoite. Both these structures are available when the eye is infected by this organism. The cyst wall resembles the plant cell wall. It is plausible that amoebae secrete cellulose because its cyst wall is primarily composed of cellulose. There is evidence which has been found to prove this matter about presence of cellulose in [28]. Therefore, it is possible to apply cellulases in controlling the pathogen which causes this disease. Cellulases can be used to break off the cyst wall and control the pathogen. However, it needs a lot of research before using cellulase as a treatment for the eye.

Pathogenic microorganisms usually form biofilms. A biofilm is an assemblage of microbial cells that is irreversibly associated (not removed by gentle rinsing)



with a surface and is enclosed in an extracellular polymeric substance (EPS) matrix. Usually pathogenic microorganisms form this type of assemblages. They may found on a wide range of surfaces including living tissues and indwelling medical devices. Artificial hip prosthesis, central venous catheter, Prosthetic heart valve, Intrauterine device and urinary catheter are some examples for indwelling medical devices that are commonly associated with biofilms. Most of the microorganisms produce extracellular polymeric substances composed of backbone structures that contain 1,3- or 1,4- β -linked hexose residues and tend to be more rigid, less deformable, and in certain cases poorly soluble. This is the exact linkages present in cellulose polymer. Therefore cellulases can be further studied for their efficient application in removing this type of biofilms from medical devices.

4.6 Food and feed industry

4.6.1 Food processing industry

Food is essential for all living organisms to obtain nutritional support for their growth and wellbeing. The huge demand for food has laid a path to a very complex, interconnected global business that supplies most of the food consumed by the world's population.

Food biotechnology nowadays considers cellulases as an invaluable resource due to their increased applicability in broad range of processes. Fruit and vegetable juice clarification, reducing the viscosity of nectars, concentrating purees, and alteration of fruits sensory properties, carotenoid extraction, olive oil extraction and the quality improvement of bakery products are among the various processes in food biotechnology that cellulase is exploited worldwide.

The cloudiness which is usually present in fruit and vegetable juices is a result of floating polysaccharide materials such as cellulose, hemicellulose, lignin, pectin, starch, metals, proteins and tannins. The presence of these materials in the juice make it low quality and draws less consumer demand. 'Rapidase pomaliq' is a commercially available enzyme preparation composed of cellulase, hemicellulases and pectinases obtained from *Trichoderma reesei* and *Aspergillus niger*. The application of this product in fruit juice clarification was beneficial to a considerable level. It is also reported that cellulase produced by bacteria such as *Bacillus* and *Paenibacillus* in combination with other enzymes such as pectinases and hemicellulases carry out the fruit and vegetable juice clarification. Apart from that, treatment Nectars and Purees also found to be efficiently carried out by this enzymatic process. Rheological parameters such as viscosity of these products are brought down to a commercially acceptable level.

Modification of sensory parameters of food is another important area where application of cellulases is highly recommended. The aroma properties, flavor, and texture of fruits are some sensory properties which play a crucial role in food biotechnology. The infusions of pectinases and cellulase enzymes have found to be effective in altering the sensory properties of fruits and vegetables [29].

These enzymes are also applied in degradation of grapes fruit peels to release sugars. These sugars will be used in many industries including food production. Another important application of cellulase is extraction of phenolic compounds from grape pomace.

During extraction of olive oil, malaxing (mixing) is an indispensable step. This period allows the tiny oil droplets to attach with bigger ones and increase the oil yield which is coming from the olive paste. The use of cellulases alone or in combination with other hydrolytic enzymes like pectinases in this step has been



found to have an enhancing effect on the extraction as well as the quality of olive oil. The enzymatic treatment of olive oil at the extraction stage causes significant enhancements in phenolic content and antioxidant activity of olive oil thereby ultimately improving its quality.

The enzyme cocktails of Cellulases with other hydrolytic enzymes such as amylases, proteases, and xylanase result in increased loaf volume, improvement in bread quality, and production of softer crumb. Enzyme cocktail containing cellulases, hemicellulases, amylases, lipases, and phospholipases results in dough conditioning with improvement of flavor, prolonged shelf life, and increase in volume after baking [30].

Another important application of cellulases is in pigment extraction from plants and plant products. Natural pigments such as carotenoids are nowadays earn a huge consumer demand as food colourants because of their natural origin, less toxicity and availability of wide range of colours. Brightly colored fruit peels such as orange, sweet potatoes, tomatoes and carrot cell walls are rich with carotenoids. These are applicable as natural food colorants. The treatment of fruit peels with enzyme cocktails including cellulase leads to carotenoid extraction.

4.6.2 Animal feed industry

In animal feed production, cellulase are applied to enhance digestibility of cereal based food and to increase nutritive values for a higher quality of forages. There are reports about efficiently using *Trichoderma* cellulase as feed additives for significant improvements in feed conversion ratio as well as digestibility of the cereal based food [31]. Forage feed of ruminants is quite complex in composition containing cellulose, hemicellulose, pectin, and lignin. There is a suggestion that it is possible to use cellulase preparations to enhance digestibility of forage [32,33]. Usually cellulase from bacteria such as *Bacillus subtilis* are used in this feed production and nutritional enhancement processes. Enzyme preparations containing cellulases and hemicellulases are utilized for numerous activities like milk yield, body weight gain, and feed. Another aspect of treating animal feed with these enzyme mixtures is to remove anti-nutritional factors present in grains and other cellulosic materials.

Furthermore, cellulases play an important part in increasing the rate and extent of fiber digestion. This can be used as a positive effect on natural gastrointestinal processes of the ruminants. The ultimate result will be the increased availability of absorbable nutrients by digestibility enhancement of fodder. The partial hydrolysis of lignocellulose materials also leads to better emulsification of food in the animal digestive tract resulting in ultimate improvement of nutrients availability.

6. Pretreatment methods of lignocellulosic biomass for bioethanol production

Energy is the life blood of modern world. Fossil fuel, among all energy sources holds the highest consumer demand. Since the industrial revolution, there is a drastic increase in fuel consumption. As fossil fuels are not renewable resources, the depletion of its natural deposits is inevitable. The scarcity of fossil fuels has not done any change in increased global demand. Therefore, we are in an era of limited and expensive energy. With the recent rise in fossil fuel prices, along with growing concern about its adverse effects on environment such as global warming caused by carbon dioxide emissions and subsequent climate change



problems, biofuels have been gaining popularity. In our study area we are focusing on bio ethanol production using cellulolytic microorganisms as well as fermentative yeast using cellulose as the substrate.

Bioethanol is a renewable form of energy. Especially, second generation bioethanol production is an emerging trend because of the abundance of low cost raw materials. The largest potential feedstock for this purpose is lignocellulosic biomass, which includes materials such as agricultural residues (corn stover, crop straws and bagasse), herbaceous crops (alfalfa, switch grass), short rotation woody crops, forestry residues, waste paper and other wastes (municipal and industrial). Lignocellulose is the most abundant renewable biomass. The yield of lignocellulose can reach approximately 200 billion metric tons worldwide per year [34]. Bioethanol production from these feedstocks has certain advantages. It is an attractive method of disposing those lignocellulosic materials which is the non-edible part of plants. Less production of pollutants makes it environment friendly. Most importantly, bioethanol production using lignocellulosic biomass does not create any food insecurity because it does not utilize any food crops before harvesting. Finally, it is abundant all around the year as a raw material.

However, the major drawback of this production process is associated with the structure of lignocellulosic biomass. It mainly consists of lignin, cellulose and hemicellulose which collectively form a very stable structure. In order to release fermentable sugars from this substrate; it needs to undergo a pretreatment process to break open the stable structure. One of the main focuses of this chapter is to discuss about the possible biological pretreatment of lignocellulosic biomass with special references to the current studies conducted by scientists. It also includes a description about our own attempts in this particular area of research.

6.1 What is biological pretreatment?

Biomass contains about 40–50% cellulose, a glucose polymer; 25–35% hemicellulose, a sugar heteropolymer; 15–20% lignin, a non-fermentable phenyl-propane unit; plus lesser amounts of minerals, oils, soluble sugars, and other components. Biological pretreatment of lignocellulosic biomass uses the ligninolytic potential of certain microorganisms (fungi and bacteria and actinomycetes) to reduce the recalcitrant nature which is mainly caused by lignin component of the feedstock and enhance its digestibility by hydrolytic enzymes [35]. The breakdown of lignin barrier changes the structure of lignocellulose and enhances the access to the cellulose and hemicellulose carbohydrate components present.

6.2 Advantages and drawbacks of biological pretreatment



Biological pretreatment seems to be a promising approach due to its low capital cost, low energy, and little dependence of chemicals, mild environmental conditions, eco-friendly nature and the absence of inhibitor generation during the process which affects in bioethanol production. Moreover, this process does not release any toxic materials or any toxic effluents to the environment.

However, there are few limitations in this strategy. The main drawback against the industrial scale application is the prolonged incubation time consumed to achieve the efficient delignification [36]. This is because of low hydrolysis rate of the microorganisms. Another possible drawback that comes into mind is the possible consumption of carbohydrates as well as fermentable sugar forms by the same microorganisms used to pretreat the material. This is possible to take place because most of the lignolytic microorganisms are producing cellulolytic enzyme batteries as well. Then the substrate left for fermentative organisms will be minimal which could consequently lead to lower bioethanol yields. Therefore it is essential to have poor cellulolytic microorganisms for delignification process.

To minimize this type of drawbacks in a biological way, it is possible to use cocultures or biofilms of efficient ligninolytic microorganisms. Introduction of fermentative yeast isolates in to the same microbial coculture would also be a perfect approach. However, developing the most efficient microbial consortium is not that simple. Excessive laboratory scale studies are required to understand the optimum physiological as well as biochemical parameter set up.

6.3 microorganisms employed in biological pretreatment

Different biological pretreatment strategies have been studied so far using different types of microorganisms. Fungi are found to be more efficient in degrading lignocellulosic biomass. For instance, White-rot fungi, Brown-rot fungi and Soft-rot fungi can be taken. First two are basidiomycetes and soft-rot fungi are classified in ascomycetes group.

Among these efficient ligninolytic microorganisms that have been studied so far, white-rot basidiomycete's fungi are found to be more versatile in the process. Most research has been concentrated on species such as *Phanerochaete chrysosporium* (*Sporotrichum pulverulentum*) which is considered as the model organisms for lignin degradation as it completely mineralizes lignin to CO₂ and water. *Ceriporiopsis subvermispora*, *Phlebia subseralis* and *Pleurotus ostreatus* *Lentinus edodes* are also some other white rot fungi that have been studied. This is thanks to the ligninolytic enzyme systems produced by these fungi. Lignin peroxidase, manganese peroxidase and laccase are the major enzymes involved in this process. Lignin peroxidase and manganese peroxidase enzymes catalyze H₂O₂-dependent oxidation of lignin while laccase which is a copper containing enzyme catalyzes demethylation of lignin components. These are a set of high redox potential Oxidoreductases.

Recently some bacterial laccases have also been characterized from *Azospirillum lipoferum*, *Bacillus subtilis* etc. Unlike fungi, the bacteria are considered as low potential for lignin degradation. However, the three groups of bacteria namely, actinomycetes, α -proteobacteria and γ -proteobacteria are known to have ligninolytic systems. Some actinomycetes were studied for their role in lignin biodegradation [37]. These degraded lignin into low molecular weight fragments. Some studies have shown potential of *Penicillium camemberti* for lignin degradation.



The biological pretreatment can be performed by growing the microorganism directly on the feedstock or using the enzyme extracts. Solid-state fermentation is the method of choice for biological delignification. Thus, from the reports available, it is evident that white rot fungi and actinomycetes can be used to remove lignin from lignocellulosic substrates. However, further studies are required to shorten the incubation time and to optimize the delignification process.

6.3 Enhancement of biological pretreatment efficiency

The importance of enhancing enzymatic hydrolysis has been increased because of the urgent need for efficient biological pretreatment processes. For this purpose it is essential to search for high enzyme -producing organisms from the natural environment. Selecting the most effective strain and its culture conditions can make the process more efficient. Another important aspect is to find unique microbial consortia for biological pretreatment. Effective biodegradation of lignocellulosic biomass takes place by biodegradation by synergistic action of microbial consortium including various bacteria and fungi. Among the several advantages of using microbial consortium which include increase adaptability, improving productivity, improving enzymatic saccharification efficiency, control of pH during sugar utilization and increasing substrate utilization [38]. With the development of biotechnology and molecular biology, the production of hyperlignolytic mutants by genetic modification of wild type species is one approach that could be studied further. Furthermore, complete understanding of the theoretical basis behind the mechanisms of actions of these hydrolytic enzyme systems is very useful in the process of enhancing hydrolytic efficiency.

Various process parameters affecting biological pretreatment like incubation temperature, incubation time, inoculums concentration, moisture, aeration and conditions of pH have to be optimized. This must be done with well –planned laboratory scale experiments. It is essential to pay attention to the microorganism used as well as the type of lignocellulosic material utilized because these parameters obviously change based on these two factors. Accessory enzymes are those enzymes which act on less abundant linkages found in plant cell walls. These include arabinases, lyases, pectinases, galactanases and several types of esterases. Some studies have reported that addition of these accessory enzymes will improve hydrolysis efficiency.

Recently, several studies have been conducted in Sri Lanka on efficient lignocellulose degrading microorganisms isolated from natural environment. Effect of co-culturing these fungal isolates for degradation of lignocellulosic material has also been reported. Co-culturing of *Trichoderma* spp. with other cellulolytic fungi has found to be improving the activity of lignocellulose degrading enzymes compared to its monocultures [36]. In a different study, 18 basidiomycetes isolates from natural environment of Sri Lanka has been evaluated for their lignocellulose degrading enzymes production. It has reported an *Earliella scabrosa* species with higher laccase activity (79600 U/l) when cultured in 50 g/l rice bran [37]. Thus, it can potentially be used for industrial production of laccase using rice bran as a cheap carbon source for high laccase production.



Conclusion(s)

The current progress in applications of cellulases is truly remarkable and attracting worldwide attention. It has already conquered the global market in an unbeatable way. Microbes are an attractive topic of interest for the production of cellulases due to their immense potential for cellulase production. However, it is apparent that more efficient species are still out there in the environment unnoticed by researchers. Further exploration and understanding of hidden mechanisms behind the activity of these enzymes are much more important. Microbial cellulases are preferred for their potential applications in broad range of industries. Their ventures are expanding day by day. More and more researches are required to produce scientific knowledge to meet the growing demands for microbial cellulase. The advances in the emerging fields such as biotechnology, microbiology and molecular biology will open up novel strategies to magnify the still- unlocked potentials of these enzymes. Eventually, it will be able to fine tune the areas which still dragging on the way to their utmost success.

Acknowledgments

Special thanks go to Research Assistant, Mr.Mohanan Kathirgamanathan and Technical officer Mrs.Kumuduni Karunarathna at Bioenergy and Soil Ecosystems Research Project, National Institute of Fundamental Studies, Kandy Sri Lanka and the National Research Council (Grant No: 12-021) for financial support.

Conflict of Interest

No conflicts of interest.

References

- [1]. O'sullivan AC. Cellulose: the structure slowly unravels. *Cellulose*.1997; 4; 173-207.
- [2]. Lavanya D, Kulkarni PK, Dixit M, Raavi PK, Krishna LNV. Sources of cellulose and their applications –A review. *International journal of drug formulation and research*.
- [3]. Davison BH, Parks J, Davis MF, Donohoe BS. Plant cell walls: basics of structure, chemistry, accessibility and the influence on conversion. In: *Aqueous Pretreatment of Plant Biomass for Biological and Chemical Conversion to Fuels and Chemicals*. 1st ed. Wyman CE: John Wiley & Sons; chapter 3, 23-38.
- [4]. Belgacem MN, Gandini A. New Materials for Sustainable Films and Coatings. In: *Biopolymers*. John Wiley & Sons; 2011. P.151-178 p. DOI: 10.1002/9781119994312.ch8
- [5]. Ciolacu D, CIOACU F, POPA VI. Amorphous cellulose – structure and characterization. *Cellulose Chem. Technol.* 2011; 45 (1-2); 13-21
- [6]. *World Enzymes to 2017*. Available from <http://www.rnrmarketresearch.com/world-enzymes-to-2017-market-report.html> [Accessed :2018-11-09]



- [7]. Vocadlo DJ, Davies GJ. Mechanistic insights into glycosidase chemistry. *Curr. Opin. Chem. Biol.* 2008; 12: 539 – 555.
- [8]. Xia L, Cen P. Cellulase production by solid state fermentation on lignocellulosic waste from the xylose industry. *Process Biochem.* 1999; 34:909-912
- [9]. McMullan G, Meehan C, Connely M. Microbial decolourisation and degradation of textile dyes. *Appl Microbiol Biotechnol.* 2001; 56: 81–87.
- [10]. Heikinheimo L, Buchert J, Miettinen-Oinonen A, Suominen P. Treating denim fabrics with *Trichoderma reesei* cellulases. *Textile Research Journal.* 2000; 70:969–973.
- [11]. Maryan AS, Montazer M. A cleaner production of denim garment using one step treatment with amylase/cellulase/laccase. *Journal of Cleaner Production.* 2013; 57: 320-326
- [12]. Cortez JM, Ellis J, Bishop DP. Cellulase finishing of woven, cotton fabrics in jet and winch machines. *J Biotechnol.* 2001; 89:239-245.
- [13]. Anish R, Rahman MS, Rao MA. Application of cellulases from an alkalothermophilic *Thermomonospora* sp. in biopolishing of denims. *Biotechnology and Bioengineering.* 2007; 96: 48–56.
- [14]. Sreenath HK, Shah AB, Yang VW, Gharra MM, Jeffries TW. Enzymatic polishing of jute/cotton blended fabrics. *Journal of Fermentation and Bioengineering.* 1996;81: 18–20
- [15]. Hebeish A, Ibrahim NA. The impact of frontier sciences on textile industry. *Colourage.* 2007; 54:41–55,
- [16]. Ibrahim NA, El-Badry KB, Eid M, Hassan TM. A new approach for bio finishing of cellulose-containing fabrics using acid cellulases. *Carbohydrate Polymers.* 2011; 83: no.1:116–121
- [17]. Mojsov K. Application of enzymes in the textile industry: A review. In: *Proceedings of the II International Congress on Engineering, Ecology and Materials in the Processing Industry*; (2011); Jahorina.
- [18]. Shah SR. Chemistry and applications of cellulase in textile wet processing. *Research Journal of Engineering Sciences.* 2013; 2: 1–5.
- [19]. Available from: <https://www.worldwildlife.org/industries/pulp-and-paper> [Accessed:2018-11-2]
- [20] Market statistics of paper industry. Available from: <https://www.statista.com/topics/1701/paper-industry/> [Accessed:2018-11-2]
- [21]. Sharma A, Tewari R, and Rana SS, Soni R, Soni SK. Cellulases: Classification, Methods of Determination and Industrial Applications. *Appl Biochem Biotechnol.* 2016. DOI 10.1007/s12010-016-2070-3
- [22]. Zhang Z J, Chen Y Z, Hu H R, Sang Y Z. The beatability-aiding effect of *Aspergillus niger* crude cellulase on bleached simao pine kraft pulp and its mechanism of action. *BioResources.* 2013; 8: 5861–5870.
- [23]. Breen A, Singleton FL. Fungi in lignocellulose breakdown and bio pulping. *Current Opinion in Biotechnology.* 1999; 10; 3: 252-258. [https://doi.org/10.1016/S0958-1669\(99\)80044-5](https://doi.org/10.1016/S0958-1669(99)80044-5)
- [24]. Garcia-Ubasart J, Torres AL, Vila C, Pastor F I J, Vidal T. Biomodification of cellulose flax fibers by a new cellulase. *Industrial Crops and Products.* 2013; 44:71–76.



- [25]. Bajpai, P. Deinking with Enzymes. Recycling and Deinking of Recovered Paper. 2014; 139–153. doi:10.1016/b978-0-12-416998-2.00008-8
- [26]. Available from: <http://www1.lsbu.ac.uk/water/enztech/detergent.html>
[Accessed: 2018-11-7]
- [27]. Rinaudo M. Chitin and chitosan: Properties and applications. *Prog Polym Sci.* 2006; 31: 603–632
- [28]. Pillai CKS, Paul W, Sharma CP. Chitin and chitosan polymers: Chemistry, solubility and fiber formation. *Prog Polym Sci.* 2009; 34: 641–678.
- [29]. Zhang J, Xia W, Liu P. Chitosan Modification and Pharmaceutical/Biomedical Applications. *Mar Drugs.* 2010; 8: 1962–1987
- [30]. Illingworth CD, Cook SD .Acanthamoeba keratitis. *Surv Ophthalmol.* 1998; 42: 493–508
- [31]. Baker RA, Wicker L. Current and potential applications of enzyme infusion in the food industry. *Trends in Food Science and Technology.* 1996; 7: 279–284.
- [32] Boutte TT, Sargent KL, Feng G. Enzymatic dough conditioner and flavor improver for bakery products. 2009. US Patent. 20090297659.
- [33] Vasco-Correa J, GeY.Li J. Biological Pretreatment of Lignocellulosic Biomass. In: *Biomass Fractionation Technologies for a Lignocellulosic Feedstock Based Biorefinery.* 2016, 561-585 P.DOI:<https://doi.org/10.1016/B978-0-12-802323-5.00024-4>. Chapter 24
- [34] Sindhu R, Binod P, Pandey A. Biological pretreatment of lignocellulosic biomass – An overview. *Bio resource Technology.* 2016; 199: 76-82
- [35] Crawford DL, Barder MJ, Pometto AL, Crawford RL
Chemistry of softwood lignin degradation by *Streptomyces viridosporus*. *Arch Microbial.* 1982; 131:140–145
- [36] Mohanan K, Ratnayake RR, Mathaniga K, Abayasekara C L, Gnanavelrajah N. Effect of co-culturing of cellulolytic fungal isolates for degradation of lignocellulosic material. *Journal of Yeast and Fungal Research.* 2014; 5(3): 31-38. DOI: 10.5897/JYFR2014.0134
- [37] Kathirgamanathan M, Abayasekara CL, Kulasooriya SA, Wanigasekera A, Ratnayake RR. Evaluation of 18 isolates of basidiomycetes for Lignocellulose degrading enzymes. *Ceylon Journal of Science.* 2017; 46(4): 77-84. DOI: <http://doi.org/10.4038/cjs.v46i4.7470>



Microbial cellulases: An overview and applications (ID: 173627)

ORIGINALITY REPORT

6%

SIMILARITY INDEX

PRIMARY SOURCES

- 1

Sharma, Amita, Rupinder Tewari, Susheel Singh Rana, Raman Soni, and Sanjeev Kumar Soni. "Cellulases: Classification, Methods of Determination and Industrial Applications", Applied Biochemistry and Biotechnology, 2016.
Crossref

176 words — 2%
- 2

medcraveonline.com
Internet

139 words — 1%
- 3

link.springer.com
Internet

119 words — 1%
- 4

Zoheb Karim, Sadaf Afrin, Qayyum Husain, Rehan Danish. "Necessity of enzymatic hydrolysis for production and functionalization of nanocelluloses", Critical Reviews in Biotechnology, 2016
Crossref

64 words — 1%
- 5

Sindhu, Raveendran, Parameswaran Binod, and Ashok Pandey. "Biological pretreatment of lignocellulosic biomass – An overview", Bioresource Technology, 2016.
Crossref

50 words — 1%
- 6

Xueming Yuan, Gang Cheng. "From cellulose fibrils to single chains: understanding cellulose dissolution in ionic liquids", Physical Chemistry Chemical Physics, 2015
Crossref

48 words — < 1%
- 7

www.statista.com
Internet

41 words — < 1%

EXCLUDE QUOTES OFF
EXCLUDE BIBLIOGRAPHY ON

EXCLUDE MATCHES OFF